

AC190 Terminal Block Mounted on the Bearing Shell

Contents

Contents of the AC190 package:

- Insulating plate
- Thermal block
- Lockplates (2)
- #5-40 mounting screws (2)
- Lockwire



Reference Documents

Install the temperature detector according to the appropriate procedure, as listed below.

Installation Instruction	Case Style	Case Diameter	Method of Installation
II #164 (formerly EI 164)	A	0.275" (7 mm)	Babbitt (Sleeve Bearing)
II #167 (formerly EI 167)	A	0.275" (7 mm)	Babbitt (Thrust Bearing)
II #180 (formerly EI 180)	B	0.188" with 0.250" ϕ flange (4,75 mm with 6,35 mm ϕ flange)	Babbitt (Thrust Bearing)
II #181 (formerly EI 181)	B	0.188" with 0.250" ϕ flange (4,75 mm with 6,35 mm ϕ flange)	Spring and Ring
II #184 (formerly EI 184)	C & D	0.125" & 0.080" (3,20 mm & 2,05 mm)	Potting

Procedure

Follow the procedure below to mount the AC190 Terminal Block on the bearing shell. This procedure is adaptable to other types of bearings and to equipment other than bearings.


Step	Action						
1	Counterbore a 1.000" + .010"/-.000" diameter hole, 0.250" deep, in the bearing shell surface at the desired location. Locate the terminal block within the leadwire length of the detector being installed.						
2	Drill and tap two holes, 0.687" apart and 0.375" deep, on the centerline of the 1" counterbore. Use a No. 39 drill and a #5-40 tap.						
3	Place the insulating plate in the counterbored hole. Place the terminal block on top of the insulating plate. Insert each machine screw through a lockplate and terminal block and into the tapped holes.						
4	Lock each screw in place by threading lockwire through the screw and lockplate, then twisting the ends of the lockwire together.						
5	Connect leadwires to AC 190 Terminal Block. <table border="1" data-bbox="203 1528 1515 1717"> <tbody> <tr> <td>A</td> <td>Place the stripped and tinned ends of the detector leadwires on the metal terminal strips and crimp the tabs over the leadwires.</td> </tr> <tr> <td>B</td> <td>Do the same with the leadwires exiting from the terminal block to the next connection points.</td> </tr> <tr> <td>C</td> <td>Solder the leadwires to the terminal strips with 60/40 alloy solder (for use to 360°F (182°C)) or with a higher temperature solder if service conditions require.</td> </tr> </tbody> </table>	A	Place the stripped and tinned ends of the detector leadwires on the metal terminal strips and crimp the tabs over the leadwires.	B	Do the same with the leadwires exiting from the terminal block to the next connection points.	C	Solder the leadwires to the terminal strips with 60/40 alloy solder (for use to 360°F (182°C)) or with a higher temperature solder if service conditions require.
A	Place the stripped and tinned ends of the detector leadwires on the metal terminal strips and crimp the tabs over the leadwires.						
B	Do the same with the leadwires exiting from the terminal block to the next connection points.						
C	Solder the leadwires to the terminal strips with 60/40 alloy solder (for use to 360°F (182°C)) or with a higher temperature solder if service conditions require.						
6	Lay the leadwires flat in the bottom of the milled groove in the bearing shell. Pot the leadwires in the groove using an epoxy, or other suitable potting compound that is compatible with bearing shell material, temperature and service conditions.						

Continued on next page

AC190 Terminal Block Mounted on the Bearing Shell, Continued

Drawing

See the drawing below for the suggested installation procedure.



Worldwide Headquarters
 7300 Commerce Lane
 Minneapolis, MN 55432 USA
 Tel: 1.763.571.3121
 Fax: 1.763.571.0927
 sales@minco.com
 www.minco.com

European Headquarters
 Usine et Service
 Commercial, Z.I.
 09310 Aston, France
 Tel: (33) 5 61 03 24 01
 Fax: (33) 5 61 03 24 09

Asia Pacific Headquarters
 20 Science Park Road
 #02-31 Teletech Park
 Singapore Science Park II
 Singapore 117674
 Tel: (65) 6511 3388
 Fax: (65) 6511 3399

ISO 9001:2000 / AS9100B

© Minco 2016
 II #107 (-)
 ECO #43979



Flex Circuits
 Thermofoil™ Heaters
 Sensors
 Instruments